

从平技术有限公司

CPDEVICE

MEGA1

THE PINNACLE OF HIGH-PERFORMANCE
RUGGED VEHICLE MOUNT COMPUTER BY CPDEVICE




V1.0



Custom-Designed Interface

- (5) Fully programmable function keys
- Dedicated recessed power button
- A-side layout for gloved operation




High-Performance SoC

- CPU: 8-core 64-bit architecture
- GPU: Supports OpenGL ES 1.1/2.0/3.2, OpenCL 2.2, Vulkan 1.2, Integrated high-performance, 2D acceleration hardware
- NPU: 6 TOPS computing power
- OS: Android 14.0 | Linux 6.1
- 8-channel camera support for:
CP AVM (Around View Monitoring)
CP DMS (Driver Monitoring System)
CP FCW (Forward Collision Warning)

Breakthrough in Omni-Communication Modes

- Cellular: 4G/5G mobile connectivity
- WiFi 6: Ultra-long range with high-speed transmission
- V2V Communication
- Handheld intercom functionality
- Dual Ethernet:
Automotive-grade Gigabit Ethernet
Legacy 100Mbps industrial Ethernet
- Industrial Interfaces:
CAN Bus
Serial ports (RS232/RS485)
Bluetooth 5.3



MEGA1


HIGH-PERFORMANCE

PINNACLE



PRODUCT SPECIFICATIONS

System	Soc CPU Octa-Core, 64 bits GPU supports OpenGL ES1.1/2.0/3.2, OpenCL 2.2, Vulkan 1.2, Built-in high-performance 2D acceleration hw NPU 6T computing power Memory 8GB RAM, Up to 8GB 32GB ROM, Up to 128GB Supports external storage via TF card slot OS Android 14.0 Linux 6.1	Display	10.1" 5-Point Capacitive Multi-touch Screen 1280*800Px, Above 750 Nits Anti-Glare Display under Strong Sunlight Supports light sensor
	Communication & Interface	AV & Sensor	720p *8/1080p *8 AHD Camera Supports CP AVM 360 Surround View System Supports CP DMS Supports Mic input Build-In Speaker Supports external audio source output
		Power	5-36V DC Input ACC Ignition Detection Power Supply Voltage Detection Reverse Voltage Protection Supports delayed power-off backup power, power failure detection, and power failure protection
Rugged Feature		Protection Level: IP65 Vibration: MIL-STD-810 Road Vehicle Standard: ISO16750 Operation Temperature: -30°C ~ +70°C Operation Humidity: 0% ~ 90%RH Storage Temperature: -40°C~ +85°C Salt Spray: 48 Hours of Salt Spray Test	
Connector		26PIN Connector *2 SMA Female Connector *1 TNC Female Connector *1 USB Type-A Connector *1	
Button	5 Function Buttons + ON/OFF Button	Mechanical Spec	Dimension (W*H*D): 270.9 * 173.5 * 33.2 mm Weight: 1.3 kg



APPLICATIONS



Precision Agriculture



Construction machine



Smart Transportation



Smart Mining



Industrial Control



Warehouse



Bridge Monitoring



Smart Port



Medicine Production

CPDEVICE
WWW.CPDEVICE.COM

